



- NOTES: 1. THE FOUNDATION HAS BEEN DESIGNED FOR A SOIL BEARING CAPACITY OF 12000#/SQ FT.
 2. THE FOUNDATION SHALL BE ON A WELDED SOIL AND SHALL BE ISOLATED ALL LEVELS.
 3. FROM THE MAIN BUILDING AND FROM OTHER FOUNDATIONS.
 4. IN FOOTING CASE, WE RECOMMEND TO CONSULT CIVIL ENGINEER, FOR EXIST DATA REQUIRED BY THE CIVIL ENGINEER SUCH AS THE WORKING OF THE MACHINE AND LANDING DATA CAN BE HAD FROM US.

- PC = DUST FILTER
- PF = OTHER FILTER
- PH = OTHER HEATER
- PI = OTHER INSULATOR
- PO = MOISTURE SEPARATOR
- PP = AFTER COOLING

NO.	REVISION	DATE	BY	REASON
1	Issued	10/10/2024	AS	Final
2	Revised	10/10/2024	AS	Final
3	Revised	10/10/2024	AS	Final

PROJECT NO. CLIENT: TITLE: LAY OUT AND FOUNDATION PLAN 2000K/HR (08L-200)

ALL DIMENSION LAYER IN MM.

This document is the property of the Engineer and is not to be reproduced or used in any manner without the written consent of the Engineering Department.